

Universe	Professional
Type	Verticality
Category	Harnesses
Subcategory	Harnesses for fall arrest, work positioning and suspension



AVAO® BOD FAST international version

The AVAO BOD FAST fall arrest, work positioning and suspension harness is designed for greater comfort in all situations. Wide, semi-rigid waistbelt and leg loops give excellent support. Its lightweight, breathable construction maximizes air flow. The shoulder straps have a system for stowing the fall arrest lanyard connectors and keeping them within reach. The DOUBLEBACK self-locking buckles at the rear of the harness, between the waistbelt and the leg loops, allow for a shorter adjustment when the dorsal attachment point is used. The harness also facilitates the carrying and organizing of work tools, with multiple equipment loops and retainers for attaching CARITool tool holders and TOOLBAG tool-holder pouches. The harness has an integrated fall indicator on the dorsal attachment point and is fastened with a TRIACT-LOCK automatic locking carabiner. It is certified to North American and European standards. AVAO BOD FAST features leg loops with FAST automatic buckles.



Wide, semi-rigid waistbelt and leg loops give excellent support. Its lightweight, breathable construction maximizes air flow.



The MGO connectors on fall arrest lanyards can be stowed on each shoulder strap. The user is thus unhindered by the lanyard, and the connectors stay within reach. In case of a fall, this system releases the MGOs and allows the absorber to be deployed.



Leg loops are equipped with FAST automatic buckles for quick and easy opening and fastening without the need to readjust them, even while wearing gloves.



Fall indicator on the dorsal attachment point: a red strap appears on the dorsal attachment point after a fall to indicate that the harness should be retired.

Short Description Comfortable harness for fall arrest, work positioning and suspension




Selling Points



- Comfortable throughout the workday:
 - wide, semi-rigid waistbelt and leg loops for excellent support. Its lightweight, breathable construction maximizes air flow
 - foam shoulder straps are widely spaced to reduce neck chafing. When the waistbelt is loaded, they help distribute the load over the shoulders
- Convenient adjustment:
 - waistbelt and shoulder straps equipped with self-locking DOUBLEBACK buckles for quick and easy adjustment
 - leg loops equipped with FAST automatic buckles for quick and easy opening and fastening without the need to readjust them, even while wearing gloves
 - stowage system for the MGO connectors on fall arrest lanyards, on each shoulder strap, allows the user to be unhindered by the lanyard and keep the connectors within reach. In case of a fall, this system releases the MGO connectors and allows the absorber to be deployed
 - side attachment points can be folded down to prevent them snagging accidentally when not in use
 - DOUBLEBACK self-locking buckles at the rear of the harness, between the waistbelt and the leg loops, allow for an adjustment for use on the dorsal attachment point. In case of a fall on this point, a shorter adjustment allows the weight to be taken up on the leg loops so that the user may remain more comfortably suspended while awaiting rescue
- Facilitates carrying and organization of tools:
 - six pre-shaped equipment loops with protective sheath
 - two slots for CARITOOL tool holder
 - four slots for TOOLBAG tool pouch
- The international version has a fall indicator: a red strap appears on the dorsal attachment point after a fall to indicate that the harness should be retired

Specification

- Ventral attachment point: attachment for a descender or a positioning lanyard for use in single mode
 - Lateral attachment points: attachment for a positioning lanyard for use in double mode
 - Sternal attachment point: fall arrest system attachment
 - Dorsal attachment point: fall arrest system attachment
 - Rear attachment point on the waistbelt: restraint lanyard attachment
 - Certification(s): ANSI Z359.11, NFPA 1983 classe III, CSA Z259.10, CE EN 361, CE EN 358, CE EN 813
 - Material(s): nylon, polyester, aluminum, steel
-

Specifications by reference

Reference(s)	C071DA00	C071DA01	C071DA02	C071DA03
				
Color(s)	black/yellow	black/yellow	black/yellow	black
Size	0	1	2	0
Waist belt	65-80 cm	70-93 cm	83-120 cm	65-80 cm
Leg loops	44-59 cm	47-62 cm	50-65 cm	44-59 cm
Stature	160-180 cm	165-185 cm	175-200 cm	160-180 cm
Weight	2350 g	2400 g	2485 g	2350 g
Made in	RO	RO	RO	RO
Guarantee	3 years	3 years	3 years	3 years
Packing	1	1	1	1
Case quantity	3	3	3	3
EAN	3342540827066	3342540827059	3342540827035	3342540827028

Reference(s)	C071DA04	C071DA05
		
Color(s)	black	black
Size	1	2
Waist belt	70-93 cm	83-120 cm
Leg loops	47-62 cm	50-65 cm
Stature	165-185 cm	175-200 cm
Weight	2400 g	2485 g
Made in	RO	RO
Guarantee	3 years	3 years
Packing	1	1
Case quantity	3	3
EAN	3342540827004	3342540826991

Spare part(s) Lanyard connector holder

Related product(s) TOOLBAG
RING OPEN
GRILLON HOOK international version
I'D® S
ASAP® international version
ASAP'SORBER international version