
# **ACCURIST®**







- Built-in rubber nosepiece.
- · Sporty design for on and off the job.
- Anti-fog lenses provide 99.9% protection against harmful UV rays.
- · Inner foam padding is flame resistant and provides excellent protection from wind, dust and other debris.
- Durable frame features dual-injected straightback temples for comfortable and secure fit against your head.

ENERAL SPECIFICATION	
ridge: 16mm	
losest Point Between Lens: 16mm	
losest Point Between Temples Tips: 95mm	
ens Base: 10 Curve	
ens Size Diagonal: 62mm	
ens Size Vertical: 35mm	
ens Thickness: 2mm	
verall Length (Lens-Tip): 116mm	
verall Width (Hinge-Hinge): 136mm	
D: 64mm	
eight: 29gm	



PACKAGING
Polybag: 1pc
Inner Box: 12 pcs
Carton: 300 pcs

COMPONENT	MATERIAL	FEATURES	
Temple	Polycarbonate/Rubber	Spatula with double injection rubber	
Frame	Nylon	Dual lens frame with side protection	
Lens	Polycarbonate	Full eye protection 10 curve lens	
Foam	RB	Fire retardant	
Hinge	Polycarbonate	Integral to frame/temple	
Screw	Stainless Steel	Standard hinge screw	

PART	LENS	LENS MARKING	FRAME MARKING
SB8710DTP	Clear Anti-Fog	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8715DTP	Coffee Anti-Fog	P + U6 L3	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8720DTP	Gray Anti-Fog	P + U6 L3	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8725DTP	Light Gray Anti-Fog	P+	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8770DP	Silver Mirror	P+	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB8775DP	Blue Mirror	P+	P Z87 + / P c SEI CAN/CSA Z94.3-07
SBR8710DTP	Clear Anti-Fog	P+U6	P Z87 + / P c SEI CAN/CSA Z94.3-07
SBR8720DTP	Gray Anti-Fog	P + U6 L3	P Z87 + / P c SEI CAN/CSA Z94.3-07
SBR8770DP	Silver Mirror	P+	P Z87 + / P c SEI CAN/CSA Z94.3-07

# **LENS MARKING**

# Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

#### **UV Filter Transmittance:**

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

### **Visible Light Filters:**

L1.3: 85% Max. Visible Light L1.7: 55% Max. Visible Light L2.5: 29% Max. Visible Light L3: 18% Max. Visible Light

# FRAME MARKING

# Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

P c SEI CAN/CSA Z94.3-07: CAN/CSA for protection devices