



Cappture™ **ANSI CE CSA**



Dielectric

Designed to better fit today's prescription eyewear

Temples extend from browbar to avoid interference with prescription frame's temples

Rubber gasket is available in select options



Part No.	Lens and Temples
S9910ST ●●●	AF Clear H2X
S9920ST ●●●	AF Gray H2X
Part No.	Rubber Gasket
S9910STMRG ●●●	AF Clear H2MAX
S9920STMRG ●●●	AF Gray H2MAX



vimeo.com/pyramex/h2max



There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European (EN166) (●) and Canadian (CSA Z94.3) (●) standards. For specific lens options visit our website or contact your sales representative.

Cappture™

General Specifications

Weight: 29.5 gm | 51.7 gm with rubber gasket
 Bridge: 23.1 mm
 Lens base: 2.5 curve
 Lens size diagonal: 145.7 mm
 Lens size vertical: 51.5 mm
 Lens thickness: 1.8 mm
 Overall length (lens - tip): 160 mm
 Overall width (hinge - hinge): 132.5mm
 Closest point between temple tips: 88 mm

Materials

Lens: polycarbonate
 Temples: polycarbonate
 Hinge: polycarbonate
 Nosepiece: polycarbonate
 Rubber gasket: polycarbonate and thermoplastic rubber (TPR)

Part No.	Lens Marking	Temple Marking
S9910ST	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
S9920ST	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
S9910STMRG	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
S9920STMRG	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices



There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967