


Class 0 ArcGuard Rubber Voltage Glove Premium Kit



Specs

Product Code KITGC0__AG

Sizes 8-12

Stock Colors



Fabric / Material Rubber/Leather

Compliance

Standards

- NFPA 70E
- CSA Z462
- ASTM F1506
- OSHA 1910.269
- ANSI/ASTM D120, Class 0, Type 1

Features

Features

- Rubber voltage gloves are electrically tested and marked with initial test date
- ArcGuard® FR knit gloves can be used with rubber voltage as a liner for added protection
- ArcGuard® FR knit gloves stretches for flexibility and dexterity
- ArcGuard® FR knit gloves RG: fits rubber voltage glove sizes 8-11
- ArcGuard® FR knit gloves LG: fits rubber voltage glove sizes 10-12
- Class 0 - Max Use Voltage 1,000V AC/1,500V DC
- Imported

Product Care

Product Care

- Should be cleaned in warm water with mild soap.
- Store flat in a protective bag. Do not fold gloves.
- Avoid high heat and high moisture areas.
- Gloves should not be placed in direct sunlight.
- Keep out of contact with any chemical substance.
- Inspections should occur before each use. Inspection methods are outlined in ASTM F1236.

Sizing Chart

ArcGuard® Rubber Voltage Gloves	
Size	Hand Circumference
8	8" or less
9	8 - 9"
10	9 - 10"
11	10" - 11"
12	11" - 12"