






Fyxate™ ANSI • CSA •






Flame resistant foam padding // Dielectric // Rubber temple tips and nosepiece // Single wraparound lens // Quick release strap

Black Temple Tips | 5 Variations

	SB10210S ●●	Clear
	SB10210ST ●●	Clear H2X AF
	SB10220S ●●	Gray
	SB10220ST ●●	Gray H2X AF
	SB10280S ●●	I/O Mirror

Foam Padded with Black Temple Tips | 3 Variations

	SB10210STMFP ●●	Clear H2MAX AF
	SB10220STMFP ●●	Gray H2MAX AF
	SB10225STMFP ●●	Light Gray H2MAX AF

Foam Padded with Lime Temple Tips | 2 Variations

	SBL10210STMFP ●●	Clear H2MAX AF
	SBL10220STMFP ●●	Gray H2MAX AF



Part No.	Lens Marking	Temple Marking
SB10210S	P Z87 + U6	P Z87 + / P c SEI Z94.3
SB10210ST	P Z87 + U6	P Z87 + / P c SEI Z94.3
SB10220S	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3
SB10220ST	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3
SB10280S	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3
SB10210STMFP	P Z87 + U6 X	P Z87 + / P c SEI Z94.3
SB10220STMFP	P Z87 + U6 L 2.5 X	P Z87 + / P c SEI Z94.3
SB10225STMFP	P Z87 + S	P Z87 + / P c SEI Z94.3
SBL10210STMFP	P Z87 + U6 X	P Z87 + / P c SEI Z94.3
SBL10220STMFP	P Z87 + U6 L 2.5 X	P Z87 + / P c SEI Z94.3

General Specifications
Weight: 23.2 gm 46.35 gm (with foam)
Bridge: 12.8 mm
Lens base: 9.5 curve
Lens size diagonal: 75.5 mm
Lens size vertical: 42.72 mm
Lens thickness: 1.95 mm
Overall length (lens - tip): 160.8 mm
Overall width (hinge - hinge): 129 mm
Closest point between temple tips: 73 mm

Materials
Lens: polycarbonate
Nosepiece: thermoplastic rubber (TPR)
Temples: polycarbonate & thermoplastic elastomers (TPE)
Temple tips: polyvinyl chloride (PVC)
Foam gasket: nylon and ethylene-vinyl acetate (EVA)
Strap: polyester

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 S: Special Purpose
 X: Tested Anti-fog

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light
 L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices