



# Poly-Torq™

## PU (Polyurethane) Gloves

### GL402C5 Series **ANSI CE**

- 13 gauge cut-resistant HPPE liner
- Tear and abrasion resistant
- Low particulate shed
- Grips well without being sticky
- Offers tactile sensitivity and dexterity

Part No.	Sizes
EGL402C5 ●●	S, M, L, XL, 2XL

#### Sizing

The color of the binding around the cuff indicates the glove size.

<span style="background-color: red; color: white; padding: 2px;">Small (7)</span> <i>Red</i>	<span style="background-color: yellow; color: black; padding: 2px;">Medium (8)</span> <i>Yellow</i>	<span style="background-color: brown; color: white; padding: 2px;">Large (9)</span> <i>Brown</i>	<span style="background-color: black; color: white; padding: 2px;">X-Large (10)</span> <i>Black</i>	<span style="background-color: blue; color: white; padding: 2px;">2X-Large (11)</span> <i>Blue</i>
---	--	---	--	---

All sizes comply with EN 420:2003 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.

#### Materials

Coating: polyurethane (PU)  
Liner shell: 13 gauge HPPE  
Cuff: HPPE & latex elastic

Country of Origin: China  
This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

#### Cleaning

Wash in warm water (30-40°C) (86-104°F)  
Use mild detergent  
Short cycle time (5-10 minutes)  
Low Tumble dry (60°C max) (140°F max)

Do not use any chemicals or sharp-edged objects for cleaning the gloves. Cleaning can alter the performance levels of the glove.



**EN388**  
**4543**

**CE** Cat. II

1,784 g



Abrasion Rated 1-4	Circular Blade Cut Rated 1-5	Tear Rated 1-4	Puncture Rated 1-4
-----------------------	---------------------------------	-------------------	-----------------------

#### Standards

**CE EN388 standard** features abrasion, cut, tear and puncture ratings. Abrasion ratings are based on the number of cycles required to abrade through the sample glove. Cut ratings are based on the number of cycles required to cut through the sample at a constant speed. Tear ratings are based on the amount of force required to tear the sample. Puncture ratings are based on the amount of force required to pierce the sample with a standard-sized point.

**ANSI standard** features cut ratings that range from A1 through A9. Cut ratings are based on the grams of weight needed to cut through the material. Our ANSI cut level glove options include A2 (500-999 grams to cut), A3 (1,000-1,499 grams to cut) and A4 (1,500-2,199 grams to cut).

#### Testing Performance

##### EN388: 2003

Abrasion (12,353)	1	2	3	4	
Cut	1	2	3	4	5
Tear	1	2	3	4	
Puncture	1	2	3	4	

##### ANSI/ISEA 105-2016

Cut	1	2	3	4	5
-----	---	---	---	---	---

There's more to see at  
**PYRAMEXSAFETY.COM**

(P) +44 (0) 1635 254220 | (E) info@pyramexeurope.com

Gloves meet European EN388:2003 (●) standards. Some meet ANSI/ISEA 105-2016 (●) standards. Gloves are sold by the dozen only. For specific options visit our website or contact your sales representative.