

GL606DPC

HPPE | Nitrile | Micro-Foam
With Dotted Palm

ANSI/ISEA 105-2016 – CUT A3
EN388: 2016 – 4X42C

Nitrile micro-foam palm coating // Dotted palm // 18 gauge HPPE liner // Reinforced thumb // Good grip in all conditions

GL606DPC S – 2XL

Suggested Applications

Assembly Line // Furniture Manufacturer // HVAC // Aerospace // Handling Oily Parts // Construction

Glove Breakdown

| |
|------------------------------|
| Type: Dipped Glove |
| Material: Nitrile Micro-Foam |
| Dots: Nitrile Smooth |
| Liner: 18 Gauge HPPE |
| Cuff: HPPE + Latex Elastic |

This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

Testing Performance

EN388: 2016 – 4X42C

| | | | | | | | | | |
|--------------------|---|---|---|---|---|---|--|--|--|
| Abrasion | 1 | 2 | 3 | 4 | | | | | |
| Circular Blade Cut | 1 | 2 | 3 | 4 | 5 | X | | | |
| Tear | 1 | 2 | 3 | 4 | | | | | |
| Puncture | 1 | 2 | 3 | 4 | | | | | |
| Cut TDM-100 | A | B | C | D | E | F | | | |
| Impact Rated | P | F | X | | | | | | |

ANSI/ISEA 105-2016

| | | | | | | | | | |
|----------|---|---|---|---|---|---|---|---|---|
| Cut | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
| Abrasion | 1 | 2 | 3 | 4 | 5 | 6 | | | |
| Puncture | 1 | 2 | 3 | 4 | 5 | | | | |



Nitrile



Abrasion



Cut



Tear



Puncture



Glove Sizing

The color of the binding around the cuff indicates the glove size.

| | | | | |
|-------|--------|-------|---------|----------|
| Small | Medium | Large | X-Large | 2X-Large |
| 7 | 8 | 9 | 10 | 11 |

All sizes comply with EN 420:2003 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.

Packaging

| |
|--------------------------|
| Pack: 12 pair |
| Case: 120 pair |
| Country of Origin: China |