

Data sheet

SKYSAFE PRO FLEX Y



GENERAL

Art. no.:	L-0623-1,8	E-class number:	40-02-01-04
EAN:	4030281202523	Customs no.:	56090000
Standard:	EN 354:2010 EN 355:2002		

Data sheet

SKYSAFE PRO FLEX Y

ONE4ALL - The SKYSAFE PRO

Revolutionary, new, patented energy absorber with the large weight range from 50 - 140kg (110 - 310 lbs.) that always withstands a maximum impact of less than 6 kN at a maximum absorber length of 1.75m (5.7 Feet).

The final impact resistance of 22 kN, also in the absorber, before AND after a fall is exceptional as well. SKYSAFE PRO furthermore meets the most relevant international standards in one SINGLE product.

UNIQUE: The built-in, adjustable RESCUE LOOPS! As a result, rescuers need not set up a rescue system and hereby save precious time in a rescue!

Available in four versions with different carabiner combinations:
I-web, Y-web, I-web tie-back, Y-web tie-back.

GENERAL

Internat. standard:

ANSI Z359.13-6/12FTFF:2013, AS/NZS

1891.1:2007, MEETS CSA Z259.11-05-E6:2010

FEATURES

Fall indicator

Breaking load, major axis:

22,00 kN

Hand-washing: 40 °C

Suitable for edges: yes

Max. service life: 10 Years

Max. number of persons: 1

Rated load: 140 KG

Patent

Rescue Loop: yes

Temperature: from 45 °C to -35 °C

Suspension element: BAND

DIMENSIONS

Size: 1,8m

Weight: 2,41 kg

HARDWARE

Carabiner on anchoring point side:

FS 64 ALU

Carabiner on belt side: KOBRA AL TRI

MATERIAL

Material: Polyester, Aluminium

Webbing material: Polyester