


<b>Universe</b>	Professional
<b>Type</b>	Verticality
<b>Category</b>	Harnesses
<b>Subcategory</b>	Fall arrest harnesses




## NEWTON international version

The NEWTON fall arrest harness is comfortable for work and easy to use. It offers ergonomic storage of MGO connectors and has fall indicators. It is certified to North American, European and Russian standards.



The sternal FAST automatic buckle allows the harness to be opened and closed simply and quickly.



The MGO connectors on ABSORBICA fall arrest lanyards can be stowed on each shoulder strap. The user is thus unhindered by the lanyard, and the connectors stay within reach. In case of a fall, a system releases the MGO connectors to allow the absorber to be deployed.



The sternal and dorsal attachment points are equipped with fall indicators: a red strap appears after a fall to indicate that the harness must be retired.

---

**Short Description** Fall arrest harness

---

**Selling Points**

- Comfortable throughout the work day: anatomical design is close-fitting, while giving optimal freedom of movement
- Easy to use:
  - color coded straps (yellow/black) provide rapid identification of the upper and lower parts of the harness before donning
  - sternal FAST automatic buckle allows the harness to be opened and closed simply and quickly
  - shoulder straps and leg loops equipped with self-locking DoubleBack buckles for quick and easy adjustment
  - stowage system for the MGO connectors on fall arrest lanyards, on each shoulder strap. In case of a fall, this system releases the MGO connectors and allows the absorber to be deployed.
  - fall indicators on the sternal and dorsal attachment points. If a fall indicator is visible after a fall, the harness must be retired.
  - two equipment loops

---

**Specification**

- Sternal attachment point: fall arrest system attachment
  - Dorsal attachment point: fall arrest system attachment
  - Certification(s): CE EN 361, EAC, ANSI Z359.11, CSA Z259.10
  - Material(s): nylon, polyester, aluminum, steel
-

**Specifications by reference**

<b>Reference(s)</b>	<b>C73AAA 1U</b>	<b>C73AAA 2U</b>
Color(s)	black/yellow	black/yellow
Size	1	2
Waist belt	70-93 cm	83-120 cm
Leg loops	47-62 cm	50-65 cm
Stature	165-185 cm	175-200 cm
Weight	1050 g	1080 g
Made in	RO	RO
Guarantee	3 years	3 years
Packing	1	1
Case quantity	5	5
EAN	3342540104822	3342540104839

---

**Accessory(ies)** CARITool  
TOOLBAG

---

**Related product(s)** MGO 110  
ASAP®