### AINSAFETY PORTABLE Gas DETECTION SOLUTIONS



AimSafety by Macurco blends more than 45-years of gas detection innovation and development into new, advanced gas monitor solutions that help organizations protect workers and the community, and increase safety, compliance and revenue.



PM150-CO<sub>2</sub>

## PM150-CO<sub>2</sub>

#### Advanced disposable single-gas, personal monitor for Carbon Dioxide

The PM150 is a low maintenance, rechargeable single-gas monitor that protects workers by providing exposure detection for carbon dioxide in many different applications. The PM150 continuously monitors ambient air conditions and provides real-time gas concentrations on an easy to read LCD display. A three-tier alarm system warns the user of the presence of unsafe carbon dioxide levels with audible, visual, and vibrating alarms. The units low, high, STEL and TWA alarms can be adjusted via the mini USB charger and software.

### **Key Features**

- Visible calibration status
- Maintenance-free
- Dual Button operation
- Event logging
- Data logging
- Rugged
- · Easy-to-read LCD display
- IP66/67 protection rating
- Rechargeable with up to 7 day run time

### **Applications**

- Wineries
- Breweries
- Food processes
- Cannabis production
- Dry ice
- Laboratory
- Manufacturing
- Refrigeration

# PM150-CO<sub>2</sub>



### **Specifications**

Size	1.6"(L) x 2.2"(W) x 3.6"(H)	
Weight	3.3 oz. (93 g.)	
Sensor Type	NDIR	
Battery	Rechargeable Li-ion	
Operating Period	Sensor ~ 7 years Battery ~ 3-5 years	
Event Logging	30 most recent events	
Data Logging	Data stored at 1 minute intervals and stores approximately 64,000 data logs	
IP Rating	IP66/IP67	
Display	LCD display with backlight	
Alarms	<ul> <li>Audible buzzer - 90 dB at 10cm</li> <li>Vibration alarm</li> <li>Flashing red LEDs</li> <li>On-screen indication</li> <li>Differentiating audible &amp; visual high and low alarm indications</li> </ul>	
Charger	Mini USB	
Set points	User Selectable via PC Software	
Temperature	-4°F to +122°F (-20°C to +50°C)	
Humidity	5% to 95% RH (Non-condensing)	
Certifications	EMC directive(2004/108/EC), RoHS2	
Warranty	2 year limited warranty	

### **Range & Resolution**

Gas	Range	Resolution
Carbon Dioxide (CO <sub>2</sub> )	0-50,000PPM or 0-5% v/v	100PPM or 0.1% v/v

### **Default Values**

PM150-CO <sub>2</sub>	Values
Low Alarm	5,000PPM (O.5% v/v)
High Alarm	10,000PPM (1.0% v/v)
STEL	30,000PPM (3.0% v/v)
TWA	5,000PPM (0.5% v/v)

#### Accessories

Part Number	Description
70-2900-0531-1	PM100/150 Bump/Calibration Hood
70-2900-0540-6	PM150 Replacement Sensor (CO2)
70-2900-0532-0	PM150 Replacement Battery
70-2900-0533-7	PM150 Replacement Front Cover
70-2900-0533-8	PM150 Mini USB Charger
70-2900-0530-5	PM100/150 Sensor Filter with Gasket (Pack of 20)
70-2900-0532-1	PM100/150/400 Monitor Clip with Screw

**Represented By:** 





Macurco Gas Detection 3601 N St. Paul Ave, Sioux Falls, SD 57104

Phone: 1-877-367-7891

Website: www.macurco.com

Email: info@macurco.com

 $\ensuremath{\mathbb C}$  Aerionics 2021. All rights reserved. Macurco is a trademark of Aerionics, Inc.

06/2021

