


Universe	Professional
Type	Verticality
Category	Mobile fall arresters
Subcategory	Ropes for mobile fall arresters



RAY 11 mm with sewn termination


The RAY 11 mm static rope with sewn termination is designed for use with an ASAP or ASAP LOCK mobile fall arrester. It has low stretch when put under tension, allowing it to meet the requirements of the ANSI Z359.15 American fall protection standard. The standard diameter ensures a good grip for easier handling. EverFlex technology guarantees great flexibility and consistent performance over time. The sewn termination with protective sheath helps keep the connector in position and facilitates handling. Rope available in five lengths.




The RAY 11 mm static rope with sewn termination is designed for use with an ASAP or ASAP LOCK mobile fall arrester.



The sewn termination with protective sheath helps keep the connector in position and facilitates handling.



EverFlex technology ensures great flexibility over time and under any conditions (water, dust, mud...), allowing it to maintain consistent handling and optimal performance with devices.



The individual identification marking on the plastic sheath allows the equipment to be tracked throughout its lifespan.

Short Description Static rope with sewn termination for use with ASAP or ASAP LOCK mobile fall arresters

- Selling Points**
- Rope with low elongation that meets the requirements of the ANSI Z359.15 standard when used with an ASAP or ASAP LOCK mobile fall arrester
 - Standard diameter ensures a good grip for easier handling
 - Consistent performance over time:
 - 100% polyester construction with a braided core
 - EverFlex technology ensures great flexibility over time and under any conditions (water, dust, mud...), allowing it to maintain excellent handling and optimal performance with devices
 - Rope with a sewn termination: this termination has a protective sheath that includes the marking, and helps keep the connector in position to facilitate handling
 - Individual identification marking on plastic sheath, to track equipment throughout its lifespan
 - Standard lengths: 25, 50, 75, 100 and 200 feet

-
- Specification**
- Diameter: 11mm
 - Material(s): polyester
 - Certification(s): ANSI Z359.15
 - Weight per meter: 98g
 - Strength with sewn termination: 26kN
 - Construction: 32 carrier
 - Percentage of sheath: 39%
 - Static elongation under 4 kN load: 3,8%
-

Specifications by reference

Reference(s)	R100BA00	R100BA01	R100BA02	R100BA03
Length	25 ft	50 ft	75 ft	100 ft
Color(s)	white	white	white	white
Made in	CZ	CZ	CZ	CZ
Guarantee	3 years	3 years	3 years	3 years
Inner pack count	1	1	1	1
Case quantity	3	3	3	2
EAN	3342540836198	3342540836204	3342540836310	3342540836327

Reference(s)	R100BA04
Length	200 ft
Color(s)	white
Made in	CZ
Guarantee	3 years
Inner pack count	1
Case quantity	1
EAN	3342540836334

Related product(s)

Bm'D
ASAP®
ASAP® LOCK
ASAP'SORBER
ASAP'SORBER AXESS