

# Rendezvous® ANSI • CE • Ballistic •



Adjustable nosepiece // Temples adjust to four different lengths // Lens angle aligns to proper position for work application with ratcheting lens pitch adjustment // Passes Ballistic MIL-PRF-32432 High Velocity Impact standards

## Black Frame | 10 Variations

	SB2810S ●●●	Clear
	SB2810ST ●●●	Clear <b>H2X AF</b>
	SB2820S ●●●	Gray
	SB2820ST ●●●	Gray <b>H2X AF</b>
	SB2830S ●●●	Amber
	SB2840S ●●●	Orange
	SB2860S ●●●	Infinity Blue
	SB2860ST ●●●	Infinity Blue <b>H2X AF</b>
	SB2870S ●●●	Silver Mirror
	SB2880S ●●●	I/O Mirror

## Crystal Gray Frame | 1 Variation

	SCG2810ST ●●●	Clear <b>H2X AF</b>
--	---------------	---------------------



SCG28

Part No.	Lens Marking	Temple Marking	General Specifications	Materials
SB2810S	P + U6	P Z87 +	Weight: 28 gm	Lens: polycarbonate
SB2810ST	P + U6	P Z87 +	PD: 68 mm	Frame: polycarbonate
SB2820S	P + U6 L2.5	P Z87 +	Bridge: 9.6 mm	Temples: polycarbonate
SB2820ST	P + U6 L2.5	P Z87 +	Lens base: 9.5 curve	Hinge: polycarbonate
SB2830S	P + U6	P Z87 +	Lens size diagonal: 83 mm	Screw: stainless steel
SB2840S	P + S	P Z87 +	Lens size vertical: 45.5 mm	Nosepiece: polycarbonate
SB2860S	P + S	P Z87 +	Lens thickness: 2.42 mm	
SB2860ST	P + S	P Z87 +	Overall width [hinge - hinge]: 138 mm	
SB2870S	P + S	P Z87 +	Closest point between temple tips: 16.6 mm	
SB2880S	P + U6 L1.7	P Z87 +	Closest point between lens: 75-76 mm	
SCG2810ST	P + U6	P Z87 +		

### Lens Marking Symbols

P: Manufacturer's mark  
 +: High impact  
 S: Special Purpose

### UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

### Visible Light Filters

L1.7: 55% Max. Visible Light  
 L2.5: 29% max visible light

### Temple Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact