



## Ridgeline<sup>®</sup> Lens Accessory

### STANDARDS

ANSI Z87.1-2020 • // CSA Z94.3-2020 •

One-piece wraparound lens for eye protection // Clips to secure the lens accessory into the safety hard hat // 5-position length adjustment provides the best fit for all head sizes // Optically correct polycarbonate lens with impact resistance against flying particles // Filters out 99.9% of all harmful UV light

-  RIDGE10STM •• Clear **H2MAX** AF
-  RIDGE20STM •• Gray **H2MAX** AF

*\*Ridgeline Lens Accessories fit both Ridgeline Cap style and Ridgeline Full Brim hard hats. Ridgeline Cap style hard hats are only CSA-approved when worn with the side clips.*



P 800.736.8673 // F 901.861.4967 // W PYRAMEX.COM



# PYRAMEX

## SPECS

### ACCESSORY MATERIALS

|             |                       |
|-------------|-----------------------|
| Lens        | Polycarbonate         |
| Nosepiece   | Polycarbonate and TPR |
| Stretch Arm | Nylon                 |
| Clip        | Nylon                 |

### WEIGHTS AND MEASURES

|                           |         |
|---------------------------|---------|
| Lens Thickness            | 2.3mm   |
| PD                        | 64mm    |
| Lens Base                 | 7 Curve |
| Weight                    | 33.4gm  |
| Vertical Lens Measurement | 54.5mm  |
| Diagonal Lens Measurement | 142.5mm |
| Bridge                    | 24.7mm  |
| Overall Length            | 171.5mm |
| Overall Width             | 167mm   |

## MARKINGS

| PART NO.   | LENS MARKING    | INNER LEFT TEMPLE MARKING | OUTER LEFT TEMPLE MARKING | INNER RIGHT TEMPLE MARKING |
|------------|-----------------|---------------------------|---------------------------|----------------------------|
| RIDGE10STM | PZ87 + U6 X     | P Z87 + TAIWAN            | <b>PMX</b>                | Ridgeline Accessory  Z94.3 |
| RIDGE20STM | PZ87 + U6 L2.5X | P Z87 + TAIWAN            | <b>PMX</b>                | Ridgeline Accessory  Z94.3 |

### LENS MARKING SYMBOLS

- P: Manufacturer's Mark
- Z87: ANSI standard for eye and face protection devices
- +: High Impact
- S: Special Purpose
- W: Welding Filter
- X: Tested Anti-fog

### UV FILTER TRANSMITTANCE

U6: .01% max effective far UV • .1% max near UV

### VISIBLE LIGHT FILTERS

- L1.7: 55% Max. Visible Light
- L2.5: 29% Max. Visible Light

### TEMPLE MARKING SYMBOLS

- P: Manufacturer's Mark
- Z87: ANSI standard for eye and face protection devices
- +: High Impact
- c SEI Z94.3: CAN/CSA standard for eye and face protection devices

