

SHOWA

386

Gray

Microporous nitrile coating over engineered DURACoil liner reinforced with HPPE.

[FEATURES

- Multifilament polyester wrapping DURACoil liner reinforced with HPPE
- EN 388:2016 Cut Level C
- ANSI/ISEA 105-16: A3
- Microporous nitrile coated palm for good grip & aeration
- Excellent fitting due to optimal liner design
- Unique SHOWA ergonomic shape that replicates the natural curve of the human hand I
- Seamless knit
- High abrasion resistance level 4

[BENEFITS

- Increased cut resistance performance due to engineered DURACoil wrapping technology
- Microporous nitrile coating protects the hand from oils and abrasions while remaining breathable
- Maximum comfort when performing delicate tasks due to soft and flexible HPPE properties combined with high multifilament wrapping technique
- High level of flexibility and dexterity due to advanced grip technology
- Ergonomically designed to replicates the natural curves for enhanced dexterity and longer use
- Embossed nitrile palm finish disperses oil away to increase grip and longevity in light oily environments.
- Cost-efficient gloves that can be laundered and re-used.

[INDUSTRY



Automotive



Construction



Engineering



Manufacturing



Mechanical

[IDEAL APPLICATIONS

- Intricate parts handling
- Brick laying
- Flashings and seals
- Maintenance
- Steel fixing
- Component Assembly



MATERIAL

- Engineered yarn
- HPPE
- Polyester

COATING

- Microporous nitrile

STANDARDS



ANSI / ISEA 105-2016



CUT

SHOWA

386

Gray



PACKAGING

- 12 Pair per polybag
- 6 Polybags per case
- 72 Pair per case



COLOUR

- Gray



SIZES

- S
- M
- L
- XL
- XXL



[YOU MIGHT ALSO BE INTERESTED IN

SHOWA
546



MATERIAL
Engineered yarn
COATING
Polyurethane

SHOWA
576



MATERIAL
Engineered yarn
COATING
Foam nitrile

SHOWA
346



MATERIAL
Engineered yarn
COATING
Latex

SHOWA
577



MATERIAL
Engineered yarn
COATING
Foam nitrile

[**USER INSTRUCTIONS**

Do not use where there are chemical, electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light.

[**DISCLAIMER**

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

Get in touch

SHOWA USA | 579 Edison Street - Menlo, GA 30731, USA

USA@SHOWAGroup.com

© SHOWA Group 2018 | All rights reserved