





















Ztek® ANSI • CE • CSA •



RUBBER TIPS

Integrated nosepiece // Soft non-slip rubber temple tips provide non-binding fit

Lens and Temples | 18 Variations

	S2510S ●●●	Clear
	S2510ST ●●●	Clear H2X AF
	S2514S ●●●	1.5 IR Filter
	S2515S ●●●	Coffee
	S2520S ●●●	Gray
	S2520ST ●●●	Gray H2X AF
	S2530S ●●●	Amber
	S2540S ●●●	Orange
	S2550SF ●●●	5.0 IR Filter
	S2560S ●●●	Infinity Blue
	S2560SF ●●●	3.0 IR Filter
	S2560ST ●●●	Infinity Blue H2X AF
	S2565S ●●●	Purple Haze
	S2570S ●●●	Silver Mirror
	S2575S ●●●	Blue Mirror
	S2580S ●●●	I/O Mirror
	S2590S ●●●	Gold Mirror
	S25ARCS ●●●	Arc – 1.5 IR Filter



Mini Ztek ANSI • CE • CSA •

Mini Ztek has all the great features of Ztek in a design better suited for slimmer facial sizes

Lens and Temples | 8 Variations

	S2510SN ●●●	Clear
	S2510SNT ●●●	Clear H2X AF
	S2517SN ●●●	Pink
	S2520SN ●●●	Gray
	S2530SN ●●●	Amber
	S2560SN ●●●	Infinity Blue
	S2575SN ●●●	Blue Mirror
	S2580SN ●●●	I/O Mirror



Mini Ztek is about 6% smaller than the Ztek.









S2514S is designed for peripheral personnel and visitors who are NOT exposed to direct IR radiation.

S25ARCS is great for use under the welding helmet – allowing welder to see work clearly without suffering “welder’s flash burn” from surrounding welders.

Ztek® Readers ANSI • CE • CSA •

Integrated nosepiece // Soft non-slip rubber temple tips provide non-binding fit

Lens and Temples | 8 Variations

	S2510R15 ●●●	Clear	+1.5 Mag
	S2510R20 ●●●	Clear	+2.0 Mag
	S2510R25 ●●●	Clear	+2.5 Mag
	S2514R15 ●●●	1.5 IR Filter	+1.5 Mag
	S2514R20 ●●●	1.5 IR Filter	+2.0 Mag
	S2520R15 ●●●	Gray	+1.5 Mag
	S2520R20 ●●●	Gray	+2.0 Mag
	S2520R25 ●●●	Gray	+2.5 Mag



S2514R is designed for peripheral personnel and visitors who are NOT exposed to direct IR radiation.



Ztek®

General Specifications

Weight: 21 gm
 PD: 68 mm
 Bridge: 13 mm
 Lens base: 10 curve
 Lens size diagonal: 64 mm
 Lens size vertical: 44 mm
 Lens thickness: 2.3 mm
 Overall length (lens - tip): 154 mm
 Overall width (hinge - hinge): 137.5 mm

Materials

Lens: polycarbonate
 Temple: polycarbonate
 Temple tips: polyvinyl chloride (PVC)
 Hinge: polycarbonate
 Screw: stainless steel
 Nosepiece: polycarbonate
 Side shields: polycarbonate

Part No.	Lens Marking	Temple Marking
S2510S	P Z87 + U6	P Z87 + / P c SEI Z94.3
S2510ST	P Z87 + U6	P Z87 + / P c SEI Z94.3
S2514S	P Z87 + R1.5S	P Z87 + / P c SEI Z94.3
S2515S	P Z87 + S	P Z87 + / P c SEI Z94.3
S2520S	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3
S2520ST	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3
S2530S	P Z87 + U6	P Z87 + / P c SEI Z94.3
S2540S	P Z87 + S	P Z87 + / P c SEI Z94.3
S2550SF	P Z87 + W5	P Z87 +
S2560S	P Z87 + S	P Z87 + / P c SEI Z94.3
S2560SF	P Z87 + W3	P Z87 +
S2560ST	P Z87 + S	P Z87 + / P c SEI Z94.3
S2565S	P Z87 + S	P Z87 + / P c SEI Z94.3
S2570S	P Z87 + S	P Z87 + / P c SEI Z94.3
S2575S	P Z87 + S	P Z87 + / P c SEI Z94.3
S2580S	P Z87 + U6 L1.7	P Z87 +
S2590S	P Z87 + S	P Z87 + / P c SEI Z94.3
S25ARCS	P Z87 + R1.5S	P Z87 + / P c SEI Z94.3

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 S: Special Purpose
 W: Welding filter
 R: IR filter
UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
Visible Light Filters
 L1.7: 55% Max. Visible Light
 L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices

Mini Ztek

General Specifications

Weight: 20 gm
 PD: 50 mm
 Bridge: 12 mm
 Lens base: 10 curve
 Lens size diagonal: 73.8 mm
 Lens size vertical: 41 mm
 Lens thickness: 2.3 mm
 Overall length (lens - tip): 144 mm
 Overall width (hinge - hinge): 128 mm

Materials

Lens: polycarbonate
 Temple: polycarbonate
 Temple tips: polyvinyl chloride (PVC)
 Hinge: polycarbonate
 Screw: stainless steel
 Nosepiece: polycarbonate
 Side shields: polycarbonate

Part No.	Lens Marking	Temple Marking
S2510SN	P Z87 H + U6	P Z87 H + / P c SEI Z94.3
S2510SNT	P Z87 H + U6	P Z87 H + / P c SEI Z94.3
S2517SN	P Z87 H + S	P Z87 H + / P c SEI Z94.3
S2520SN	P Z87 H + U6 L2.5	P Z87 H + / P c SEI Z94.3
S2530SN	P Z87 H + U6	P Z87 H + / P c SEI Z94.3
S2560SN	P Z87 H + S	P Z87 H + / P c SEI Z94.3
S2575SN	P Z87 H + S	P Z87 H + / P c SEI Z94.3
S2580SN	P Z87 H + U6 L1.7	P Z87 H + / P c SEI Z94.3

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 S: Special purpose
 H: Small head size
UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light
 L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 H: Small head size
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices

Ztek® Readers

General Specifications

Weight: 21 gm
 PD: 68 mm
 Bridge: 13 mm
 Lens base: 10 curve
 Lens size diagonal: 64 mm
 Lens size vertical: 44 mm
 Lens thickness: 2.3 mm
 Overall length [lens - tip]: 154 mm
 Overall width [hinge - hinge]: 137.5 mm

Materials

Lens: polycarbonate
 Temple: polycarbonate
 Temple tips: polyvinyl chloride (PVC)
 Hinge: polycarbonate
 Screw: stainless steel
 Nosepiece: polycarbonate
 Side shields: polycarbonate

Part No.	Lens Marking	Temple Marking	
S2510R15	P Z87 + U6	+1.50	P Z87 - 2+ / P c SEI Z94.3
S2510R20	P Z87 + U6	+2.00	P Z87 - 2+ / P c SEI Z94.3
S2510R25	P Z87 + R1.5S	+2.50	P Z87 - 2+ / P c SEI Z94.3
S2514R15	P Z87 + R1.5S	+1.50	P Z87 - 2+
S2514R20	P Z87 + R1.5S	+2.00	P Z87 - 2+
S2520R15	P Z87 + U6 L2.5	+1.50	P Z87 - 2+
S2520R20	P Z87 + U6 L2.5	+2.00	P Z87 - 2+
S2520R25	P Z87 + U6 L2.5	+2.50	P Z87 - 2+

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 S: Special Purpose
 R: IR filter
UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
Visible Light Filters
 L2.5: 29% max visible light

Temple Marking Symbols

+1.50: magnification of +1.5
 +2.00: magnification of +2.0
 +2.50: magnification of +2.5
 P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 - 2: Rx
 +: High impact
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices