Universe	Professional
Type	Verticality
Category	Harnesses
Subcategory	Fall arrest and work positioning harness

VOLT® LT

The fall arrest and work positioning VOLT LT harness is very easily donned thanks to its EASYFIT design: a vest ensures the harness keeps its shape and the FAST automatic buckles on the waistbelt and leg loops allow the harness to be donned with both feet on the ground. The VOLT LT harness' anatomical design and wide, semi-rigid waistbelt ensure comfort throughout the work day. It is certified to U.S. and European standards.

The EASYFIT concept integrates a vest that ensures the harness keeps its shape, and FAST automatic buckles (waistbelt and leg loop) that allow the harness to be donned with both feet on the ground.

Short Description	Fall arrest and work positioning harness
Selling Points	• Rapid donning thanks to the EASYFIT design: - vest ensures the harness keeps its shape - FAST automatic buckles on the waistbelt and leg loops allow the harness to be very easily donned, with both feet on the ground. These buckles retain their adjustment settings between donnings. • Comfortable throughout the work day: - anatomical design is close-fitting, while giving optimal freedom of movement - lightweight, breathable construction - wide, semi-rigid waistbelt for excellent support - leg loop foam position can be adjusted for perfect positioning - side slots allow a seat to be installed for greater comfort in prolonged suspension • Easy to use: - waistbelt and shoulder straps equipped with self-locking DoubleBack buckles for quick and easy adjustment - side attachment points can be folded down to prevent them snagging accidentally when not in use - stowage system for the MGO connectors on fall arrest lanyards, on each shoulder strap. In case of a fall, this system releases the MGO connectors and allows the absorber to be deployed. - fall indicators on the sternal and dorsal attachment points. If a fall indicator is visible after a fall, the harness must be retired. - equipment loops, slots for CARITOOL tool holder and TOOLBAG tool pouch allow easy organization of work tools
Specification	• Side attachment points: for attaching a positioning lanyard for use in double mode • Sternal attachment point: for attaching a fall arrest system • Dorsal attachment point: for attaching a fall arrest system • Rear waistbelt attachment point: for attaching a restraint lanyard • Certification(s): ANSI Z359.11, CE EN 361, CE EN 358 • Material(s): nylon, polyester, aluminum, steel

Specifications by reference

Reference(s)	**C72AFA 0U**	**C72AFA 1U**	**C72AFA 2U**
Size	0	1	2
Waist belt	65-80 cm	70-93 cm	83-120 cm
Leg loops	44-59 cm	47-62 cm	50-65 cm
Stature	160-180 cm	165-185 cm	175-200 cm
Weight	1850 g	1895 g	2000 g
Made in	RO	RO	RO
Guarantee	3 years	3 years	3 years
Packing	1	1	1
Case quantity	3	3	3
EAN	3342540105003	3342540104990	3342540104983

Accessory(ies)

CARITOOL
TOOLBAG
LIFT
Seat for VOLT® harnesses

Related product(s)

GRILLON